


Tolerances/Tolerance  $\frac{1SD}{2768-M}$   $>0.5=3 \pm 0.1$   $>3=6 \pm 0.1$   $>6=30 \pm 0.2$   $>30=120 \pm 0.3$   $>120=400 \pm 0.5$   $>400=1000 \pm 0.8$

Config Table

SKU#	Power Cord Length	Plug
AP51001	-	-
AP51001-20	6mm <sup>2</sup> x3, 2M	-
AP51001-20P	6mm <sup>2</sup> x3, 2M	IEC309 32A 3P6H IP44

PUD Series: Meter By Bank  
 Input: 200-240V AC, 32A, 1Ph  
 Outlet: C13 [18], C19 [6].  
 CB/Bank: 16A/1P [2], 2xBank  
 Outlet Color: Black/Red  
 Chassics Color: Black



IEC609 PLUG  
IP44 32A 3P6H

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF A-RACK AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM A-RACK. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

Drawn by	Description	Drawing No.
Approved by	Meter PDU, 200-240V AC, 32A, 1Ph C13 [18], C19 [6]	AP51001
	Version	Third Angle Projection
	A1	A4
Scale:	Unit: mm	Sheet: 1 OF 1
1:-		